

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

74000-00105, ink, yellow

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

printer's ink
Ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Paul Leibinger GmbH & Co. KG
Daimlerstrasse 14
78532 Tuttlingen

Telephone no. +49 (0)7461 9286 0
Fax no. +49 (0)7461 9286 119
e-mail info@leibinger-group.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319
Flam. Liq. 2; H225
STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

butanone

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378 In case of fire: Use sand, fire powder, carbon dioxide or foam to extinguish.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	butanone		
	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 70.00 - < 90.00 wt%
2	Tetrabutylammonium nitrate		
	1941-27-1 217-726-0 - -	Ox. Sol. 2; H272 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	< 5.00 wt%
3	n-butyl acetate		
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	< 5.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting adverse effects, consult a physician.

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off with water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get medical attention if pain still persists.

After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources.

For emergency responders

Personal protective equipment (PPE) - see section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and after work. Remove contaminated clothing and shoes and launder thoroughly before reusing.

Advice on protection against fire and explosion

Keep away from ignition sources and provide for good ventilation. Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place.

Recommended storage temperature

Value 10 - 25

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)**Recommendations**

Ink for industrial CIJ printers

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
	2000/39/EC		
	Butanone		
	WEL short-term (15 min reference period)	900 mg/m ³	300 ppm
	WEL long-term (8-hr TWA reference period)	600 mg/m ³	200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Butan-2-one		
	WEL short-term (15 min reference period)	899 mg/m ³	300 ppm
	WEL long-term (8-hr TWA reference period)	600 mg/m ³	200 ppm
	Comments	Sk, BMGV	
2	n-butyl acetate	123-86-4	204-658-1
	List of approved workplace exposure limits (WELs) / EH40		
	Butyl acetate		
	WEL short-term (15 min reference period)	966 mg/m ³	200 ppm
	WEL long-term (8-hr TWA reference period)	724 mg/m ³	150 ppm
	EU 2019/1831		
	n-Butyl acetate		
	WEL short-term (15 min reference period)	723 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	241 mg/m ³	50 ppm

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name	CAS / EC no
	Route of exposure	Value
	Exposure time	
	Effect	
1	butanone	78-93-3

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

				201-159-0
	dermal	Long term (chronic)	systemic	1161 mg/kg/day
	inhalative	Long term (chronic)	systemic	600.00 mg/m ³
2	n-butyl acetate			123-86-4 204-658-1
	dermal	Long term (chronic)	systemic	11 mg/kg/day
	dermal	Short term (acute)	systemic	11 mg/kg/day
	inhalative	Long term (chronic)	systemic	300 mg/m ³
	inhalative	Short term (acute)	systemic	600 mg/m ³
	inhalative	Long term (chronic)	local	300 mg/m ³
	inhalative	Short term (acute)	local	600 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	butanone			78-93-3 201-159-0
	oral	Long term (chronic)	systemic	31 mg/kg/day
	dermal	Long term (chronic)	systemic	412 mg/kg/day
	inhalative	Long term (chronic)	systemic	106 mg/m ³
2	n-butyl acetate			123-86-4 204-658-1
	oral	Long term (chronic)	systemic	2 mg/kg/day
	oral	Short term (acute)	systemic	2 mg/kg/day
	dermal	Long term (chronic)	systemic	6 mg/kg/day
	dermal	Short term (acute)	systemic	6 mg/kg/day
	inhalative	Long term (chronic)	systemic	35.7 mg/m ³
	inhalative	Short term (acute)	systemic	300 mg/m ³
	inhalative	Long term (chronic)	local	35.7 mg/m ³
	inhalative	Short term (acute)	local	300 mg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	butanone		78-93-3 201-159-0
	water	fresh water	55.8 mg/L
	water	marine water	55.8 mg/L
	water	Aqua intermittent	55.8 mg/L
	water	fresh water sediment	284.74 mg/kg
	with reference to: dry weight		
	water	marine water sediment	284.7 mg/kg
	with reference to: dry weight		
	soil	-	22.5 mg/kg
	with reference to: dry weight		
	sewage treatment plant	-	709 mg/L
	secondary poisoning	-	1000 mg/kg
	with reference to: food		
2	n-butyl acetate		123-86-4 204-658-1
	water	fresh water	0.18 mg/L
	water	marine water	0.018 mg/L
	water	Aqua intermittent	0.36 mg/L
	water	fresh water sediment	0.981 mg/kg dry weight
	water	marine water sediment	0.0981 mg/kg dry weight
	soil	-	0.0903 mg/kg
	sewage treatment plant	-	35.6 mg/L

Trade name: 74000-00105, ink, yellow**Current version :** 1.0.0, issued: 11.03.2021**Replaced version:** -, issued: -**Region:** GB**8.2 Exposure controls****Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

State of aggregation		
liquid		
Form/Colour		
yellow		
Odour		
acid		
pH value		
No data available		
Boiling point / boiling range		
Value	79	°C
Source	supplier	
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Value	-8	°C
Source	supplier	
Ignition temperature		
No data available		
Auto-ignition temperature		
Value	415	°C
Source	supplier	

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

Flammability			
No data available			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			
Value	10.15	hPa	
Reference temperature	18.49	°C	
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	7.28	lbs/gallon	
Source	supplier		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
log Pow		0.3	
Reference temperature		40	°C
Method	OECD 117		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		
Viscosity			
No data available			
Particle characteristics			
No data available			

9.2 Other information

Other information	
Temperature class (EU ATEX): T2	

SECTION 10: Stability and reactivity

10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

Oxidizing agents

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
LD50		2054	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA / Read across		
2	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50		14112	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity			
No data available			

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
2	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
2	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

1	butanone	78-93-3	201-159-0
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	In vitro Mammalian Chromosomal Aberration Test		
Species	rat		
Method	OECD 473		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	In vitro mammalian cell gene mutation test		
Species	Mouse lymphoma cells		
Method	OECD 476		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus		
Species	mouse		
Method	OECD 474		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Route of exposure	inhalational		
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Route of exposure	inhalational		
Species	rat		

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

Method	OECD 413
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	n-butyl acetate
	123-86-4
	204-658-1
Route of exposure	inhalational
NOAEC	500
Duration of exposure	90
Species	rat
Method	EPA OTS 798.2450
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard

No data available

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
LC50		2993	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
EC50		308	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
----	----------------	---------	--------

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

1	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species with reference to	Daphnia magna		
Method	CAS 110-19-0		
Source	OECD 211		
Evaluation/classification	ECHA		
	Based on available data, the classification criteria are not met.		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
EC50		2029	mg/l
Duration of exposure		96	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
2	n-butyl acetate	123-86-4	204-658-1
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		
Half-life		3.3	day(s)
Reference temperature		25	°C
Source	ECHA		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF		15.3	
Method	Calculation model used (Q)SAR		

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

Source		ECHA	
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
log Pow		0.3	
Reference temperature		40	°C
Method		OECD 117	
Source		ECHA	
2	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method		OECD 117	
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1210
Proper shipping name	PRINTING INK
Special Provision 640	640C
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1210
Proper shipping name	PRINTING INK
EmS	F-E, S-D
Label	3

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021

Replaced version: -, issued: -

Region: GB

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1210
Proper shipping name	Printing ink
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226	Flammable liquid and vapour.
H272	May intensify fire; oxidiser.

Trade name: 74000-00105, ink, yellow

Current version : 1.0.0, issued: 11.03.2021**Replaced version:** -, issued: -**Region:** GB

H315 Causes skin irritation.
H335 May cause respiratory irritation.

Creation of the safety data sheet

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357,
e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 772713